

Installation Instructions for MV110, MV115, MV120, MV125 Highway pegs and Mounts

This set of pegs and mounts are from our Import “value line” of products, they are not made by us nor here in the USA. They are very functional, stylish and a good choice for the budget minded consumer however they may have small flaws in the polishing and plating not seen in our premium US made products. They carry a six months warranty whereas our US made products carry a two year warranty.

1. Lay the enclosed parts out and familiarize yourself with them. Remove the large bolt from the clamp and arm. Place the clamp around the tube of the engine guard with the bolt hole facing outward. Place the black plastic washer between the clamp halves at the bolt hole. Install the bolt with arm onto the clamp, raise it to the desired height and angle then tighten loosely. Repeat this on the other side.
2. Remove the Allen bolt flat shim and spring shim from the peg mounting slot at the end of the arm. Using only the bent or curved spring shim place the shim into the slot with its flat side or edge at the bottom of the slot and the bend facing the peg, insert the pegs male clevis into the slot (notice there is a left and right peg and install them accordingly). Align the holes of the peg, bracket and shim using one of the supplied Allen wrenches or a Phillips screwdriver. Place a drop of thread locker (Loc-Tite) onto the threads on the peg mounting bolts then install the bolts and tighten to 8-12 ft. lbs. Note: Over tightening will not allow the peg to fold up smoothly, if at all.
3. Adjust the height and angle of the arms and pegs as desired and so they are the same on both sides. Notice that the pegs can be rotated on their male mounting clevis or tab. This is done with the bolt at the outer end of the peg on some models. With others you will need to first remove the rubber pad by removing the screws which hold them in place. This will then give you access to the bolt the peg rotates on.
4. Tighten the large clamp bolts securely (25-30 ft. lbs.)



RIVCO Products, Inc.
440 S. Pine Street, Burlington, WI 53105
262-763-8222 rivcoproducts.com